III. A.31 High Capacity





LK-43K

Rough Terrain High-Capacity Forklifts

STANDARD EQUIPMENT

60" Shaft-type carriage, 48" forks, Air brakes, roller mast, hydrostatic steering, dual front tires, mast side shift. Lighting kit includes two headlights and two tail lights. Safety group includes overhead guard, safety flasher, back-up alarm, electric horn, suspension seat with seat belt and anti-vandalism kit. Also includes diesel cold start kit, differential lock, and block heater. Gauge group consists of hour meter, fuel, volt meter and engine temperature indicator.

OPTIONAL EQUIPMENT

Enclosed walk-through cab complete with heater, defroster fan, windshield wiper, dome light, sliding window, lift-off removable doors, and sound insulation. Also optional are forks from 60" to 96", 3 section mast, freelift, clearview, mast buckets, gas engine, propane engine, catalytic muffler, hi-mount air cleaner, extra work lights, engine air pre-cleaner, outside rear-view mirrors, rotating beacon, extra control valve and handle, hydraulic accumulator, tachometer, mast mounted guarded lights, fire extinguisher, dead man seat, additional parts manual, operators manual and service manuals.

LIFTKING®



7135 Islington Avenue Woodbridge, Ontario Canada L4L IV9 Tel: (905) 851-3988 Fax: (905) 851-6396 info@liftking.com www.liftking.com Toll Free: I 888 LIFTKNG

The information contained herein is general in nature and it is not intended for specific application purposes. LIFTKING® reserves the right to make changes in specifications shown, herein, and improvements, or discontinue manufacture at any time without notice or obligation.

SPECIFICATIONS

ATIONS LK•43K

GENERAL

BRAKES:

Type of Vehicle	Liftking Model LK43K Diesel,
	High-Capacity Forklift
Manufacturer	Liftking Industries Incorporated
Rated Capacity	43,000 lbs at 48 in Load Center
Length (Less Forks)	202 in / 5.1 m
Overall Width	109 in / 2.8 m
Height Overhead Guard	118 in / 3.0 m
Lowered Mast Height	118 in / 3.0 m
Max. Lift Height	100 in / 2.5 m
Max.Tilt Forward	10 degrees
Max.Tilt Backward	10 degrees
Ground Clearance	10 in / 25 cm
Wheel Base	157 in / 4 m
Weight, No Load	48,500 lb / 22,019 kg
Turning Radius	219 in / 5.6 m

ENGINE:	Diesel Cummins, Model 6BT5.9-0
	160 hp, 6 cylinders, Turbocharged
TRANSMISSION:	Powershift, 3 Speeds Forward
	3 Speeds Reverse
TIRES:	Front - Dual - 14.00R25
	Rear - Single - 14.00R25

2-Wheel, Air



The LK43K features dual-front tires and a heavy duty roller mast.



The LK43K is available with a two-door walk-through cab, complete with heater, defroster fan, windshield wiper, dome light, sliding window, lift-off removable doors and sound insulation.



The LK43K features a large engine panel for easy access to the engine compartment, making service and maintenance tasks easier.



This new generation of Liftking Forklifts features a onepiece steering column with gauges and controls conveniently situated, leaving additional room in the operator's compartment.



Truck Mounted forklifts

Your local authorized dealer