

Electric Platform Truck

Model:
BD20/25/30



1KG=2.205LB 1INCH=25.40MM

Model		BD20	BD25	BD30
Drive type		battery	battery	battery
Load capacity	Q(kg)	2000	2500	3000
Axle loading, laden front/rear	kg	1104/2346	975/2825	1660/3090
Axle loading, unladen front/rear	kg	676/774	590/710	865/885
Tyre size, front		6.00-9-10PR	16x5x10 1/2	6.00-9-10PR
Tyre size, rear		6.50-10-12PR	18x5x12 1/2	6.50-10-12PR
Wheels, number front rear(x=driven wheels)		2/2x	2/2x	2/2x
Seat height/stand height	h ₁ (mm)	800	770	820
Coupling height	h ₂ (mm)	500	400	550
Loading height, unladen	h ₃ (mm)	740	620	780
Length of loading surface	l ₁ (mm)	2000	2000	2240
Overhang	l ₂ (mm)	630	770	630
Width of loading surface	b ₁ (mm)	1250	1100	1400
Overall length	l ₃ (mm)	3200	3150	3440
Overall width	b ₁ /b ₂ (mm)	1250	1100	1400
Turning radius	W ₁ (mm)	3250	2900	3580
Internal turning radius	b ₃ (mm)	1400	1040	1500
Travel speed, laden/unladen	Km/h	11/13	9/12	11/13
Battery voltage, nominal capacity K5	V/Ah	48/330	48/250	48/395
Battery weight	Kg	662	430	774
Battery dimensions l/w/h	mm	740x426x505	740x426x390	740x426x505
Service weight. (with battery)	Kg	1450	1300	1750

